



Date:	3/11/09	MSDS No:	
Supersedes:			
Trade Name:			
Sizes:	All		

MATERIAL SAFETY DATA SHEET

SECTION I - IDENTIFICATION

Manufacturer/Supplier: Dial Manufacturing, Inc. 25 S. 51st Avenue Phoenix, Arizona 85043 Tel. No.: (602) 278-1100	Product Name:	COOLER COVER
	Product Type:	Finishing Treatment Used On Canvas Cooler Covers
	Product Number(s):	8301 thru 8650

SECTION II – HAZARDOUS MATERIALS

Canvak Coating is a mixture of chemicals, the identities of which are being withheld pursuant to the trade secret exemption set forth at 29 C.F.R. Sections 1910.1200(g)(2)(i) and (1)(1)(i)

SECTION III – PHYSICAL DATA

Boiling Point:	N/A	Appearance and Odor:	Waxy solid, slight odor
Vapor Pressure (mm Hg):	N/A	Specific Gravity (H₂O=1)	55%
Vapor Density (Air=):	(Butyl Acetate = 1)	Melting Point:	120° F
Solubility in Water:	Material is insoluble	Evaporation Rate:	N/A

SECTION IV – FIRE AND EXPLOSTION HAZARD DATA

Flash Point:	N/A	Flammable Limits:	N/A
Extinguishing Media:	Water or any media suitable for source.	Evaporation Rate:	N/A
Special Fire Fighting Procedures:	Self-contained breathing equipment	Unusual Fire and Explosion Hazards:	N/A

SECTION V – REACTIVITY DATA

Stability:	Material is Stable
Incompatibility (materials to avoid):	Strong Acids
Hazardous Decomposition or Byproducts:	None
Hazardous Polymerization:	Will not occur

SECTION VI – HEALTH HAZARD DATA

Individual Components of Canvak Coating

Health hazards/signs and symptoms of exposure

Eye:	<u>Acute</u> – Exposure to fumes of two components of coating may cause temporary eye irritation. Contact with eyes by two components upon heating may produce eye burns.
Skin:	<u>Acute</u> – Exposure to two components of coating may cause skin irritation or reaction. Exposure to one component of coating may cause, in extreme cases, inflammation, cracking, and a possible secondary infection. Contact with skin by two components upon heating may produce skin burns.
Inhalation:	<u>Acute</u> – Inhalation of three components of coating may cause irritation of the respiratory tract. Excessive inhalation of one component may cause dizziness and central nervous system depression.
Ingestion:	<u>Acute</u> – Ingestion of three components of coating may cause harm, including gastrointestinal disturbances and intestinal obstruction.
Carcinogenicity:	Canvak contains no listed carcinogens to which downstream employees may be exposed.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:	If melted material is spilled, contain material, let cool and harden, then remove.
Waste Disposal Method:	Dispose in accordance with all local, state and federal regulations.
Precautions to be taken in Handling and Storage:	A good ventilation system and eye protection is strongly recommended during heating, melting, and handling of solid Canvak.
Other Precautions:	Thin protective gloves should be worn if dermatitis occurs.

SECTION VIII – CONTROLS MEASURES

Respiratory Protection:	None
Ventilation:	Local exhaust is recommended.
Protective Gloves:	Recommended
Eye Protection:	Strongly recommended during heating and melting of sold Canvak.
Work/Hygiene Practices:	Good industrial hygiene practice is recommended.